



# Flat Panels

Great Features:

- Aluminium Frame
- Polycarbonate Diffuser
- Easy Recessed Installation



SPECIFICATIONS	Dimmable Driver		Dimmable Driver	
	Cat No: <b>FP3001200-S</b>	Cat No: <b>FP3001200D-S</b>	Cat No: <b>FP1501200-S</b>	Cat No: <b>FP1501200D-S</b>
Size:	300mm wide x 1200mm	300mm wide x 1200mm	150mm wide x 1200mm	150mm wide x 1200mm
Protection Rating:	IP44	IP44	IP44	IP44
Input:	200-240VAC	200-240VAC	200-240VAC	200-240VAC
Power Frequency:	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz
Power Factor:	>0.9	>0.9	>0.9	>0.9
Beam Angle:	120°	120°	120°	120°
LED Power:	40W	40W	22W	22W
LED Efficiency:	80-90lm/W	80-90lm/W	80-90lm/W	80-90lm/W
LED Luminous Flux:	3600lm	3600lm	1850-1980lm	1850-1980lm
LED Colour Temperature:	4000K	4000K	4000K	4000K
LED Life Time:	>30,000 Hours	>30,000 Hours	>30,000 Hours	>30,000 Hours
Working Temperature:	-30°~+55°	-30°~+55°	-30°~+55°	-30°~+55°
Driver:	SAA Approved Driver	SAA Approved DSI Dimmable Driver	SAA Approved Driver	SAA Approved DSi Dimmable Driver



	<b>VIC</b>	<b>NSW</b>	<b>QLD</b>	<b>SA</b>	<b>WA</b>
Telephone:	(03) 8793 9700	(02) 9734 9944	(07) 3283 1199	(08) 8345 0017	(08) 9271 9787
Facsimile:	(03) 8793 9777	(02) 9734 9933	(07) 3283 1170	(08) 8345 0118	(08) 9271 8981

Web/Email: [www.omegapower.com.au](http://www.omegapower.com.au) / [sales@omegapower.com.au](mailto:sales@omegapower.com.au)